


500-700mW Single Mode Pump Lasers

Features

- Tested to Telcordia GR-468-CORE
- Optional Bragg grating
- Internal cooler and thermistor

Applications

- Telecom
- CATV
- Defense
- Life Science



General Description

The Gooch & Housego line of single mode, cooled 980 nm pump lasers deliver up to 700mW of fiber-coupled power. The modules are packaged using the unique, patent pending technology Uniline™ for permanent fiber alignment. Uniline™ provides superior end-of-life optical and electrical performance, achieved by maintaining a highly stable, all-axis alignment lock between the laser chip and the tip of the single-mode fiber.

The hermetically sealed 14 pin butterfly package is available with a fiber Bragg grating and includes thermoelectric cooler, thermistor, monitor photodiode and UniDry™ getter. The fiber Bragg grating precisely locks the center wavelength over extended power and temperature range. Center wavelengths in the range of 976 nm to 980 nm are available with tight wavelength control. G&H's Uniline™ family of pump lasers are tested to meet the requirements outlined in Telcordia GR-468-CORE.

Absolute Maximum Ratings

Stresses beyond those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. These are stress ratings only and operation of the device at these or conditions beyond these are not implied. Exposure to absolute maximum ratings for extended periods of time may affect device reliability.

Parameter	Sym.	Condition	Min	Max	Unit
Storage Temperature	T _{STG}		-40	+85	°C
Operating Case Temperature	T _{OP}		-20	+65	°C
Laser Forward Current	I _F			1.2	A
Laser Reverse Voltage	V _R			2.5	V
Photo Diode Photo Current	I _{PD}			10	mA
Photo Diode Reverse Voltage	V _{PD}			20	V
TEC Current	I _{TEC}			6.0	A
TEC Voltage	V _{TEC}			4.0	V
Thermistor Current				2	mA
Thermistor Voltage				5	V
Lead Soldering Time				10	s
Lead Soldering Temperature				250	°C
ESD		HBM		500	V

500-700mW Single Mode Pump Lasers

Optical Characteristics

$T_{op}=25^{\circ}\text{C}$, continuous wave and beginning of life unless otherwise specified.

Parameter	Sym.	Condition	Min	Typ	Max	Unit
Operating Chip Temperature	T_{CHIP}		20		35	$^{\circ}\text{C}$
KINK Power	P_{op}	$I=I_{KINK}$	See ordering information			mW
Center Wavelength	λ_c	$P=P_{op}$	See ordering information			nm
Wavelength Tolerance	$\Delta\lambda$	With Fiber Bragg Grating	-1		1	nm
		Without Fiber Bragg Grating	-5		5	
Spectral Shift With Temperature	$\Delta\nu$	With Fiber Bragg Grating			0.2	nm/ $^{\circ}\text{C}$
		Without Fiber Bragg Grating		0.35		
Power In Band		@ $\lambda_c \pm 1\text{nm}$, $P>50\text{mW}$	90			%

Electrical Characteristics

Parameter	Sym.	Condition	Min	Typ	Max	Unit
Threshold Current	I_{TH}				55	mA
Laser Drive Current	I_{op}		See ordering information			mA
Laser Forward Voltage	V_F	$I=I_{op, MAX}$			2.7	V
Monitor Photo Diode Current	I_{PD}	$P=P_{op}$	0.1		6.0	mA
Monitor Photo Diode Dark Current	I_D				100	nA
TEC Current		$\Delta T=25^{\circ}\text{C}$, $P=P_{op}$			3.5	A
TEC Voltage		$\Delta T=25^{\circ}\text{C}$, $P=P_{op}$			3.5	V
Thermistor Resistance	R_{TH}	$T=25^{\circ}\text{C}$	9500	10000	10500	Ω
Thermistor β Coefficient	β	0 / 50°C		3892		





Fiber Specification

Parameter	Sym.	Condition	Min	Typ	Max	Unit
Fiber Type				PM		
Jacket Material				Hytrel Acrylate		
Core Diameter			5.6	6.6	7.6	μm
Cladding Diameter			123	125	127	μm
Buffer Diameter			230	245	260	μm
Pigtail Length With Grating			1.5	3		m
Pigtail Length Without Grating			1.0	1.3		m
Proof Strength			120			kpsi

500-700mW Single Mode Pump Lasers


Typical Operating Characteristics

T_{op}=25°C




Pinout and Mechanical Drawing

Pin	Description	Pin	Description
1	TEC+	14	TEC-
2	Thermistor	13	Case GND
3	Monitor PD Anode	12	NC
4	Monitor PD Cathode	11	Laser Cathode
5	Thermistor	10	Laser Anode
6	NC	9	NC
7	NC	8	NC



500-700mW Single Mode Pump Lasers

Ordering Information

AC1401	XXXX	YYYY	ZZ	Parameter	Option	Description
	Grating Type	SM	SM Grating			
		PM	PM Grating			
		00	No Grating (free running)			
	Wavelength [nm]	0974	974nm			
		0976	976nm			
		0978	978nm			
		0980	980nm			
	Power [mW]	0500	500mW			
		0600	600mW			
		0700	700mW			
	Product Family	AC1401	Single Mode Laser			

Typical Characteristics

Device	Max Kink Free Power [mW]	Typical Kink Current [mA]	Typical Operating Power [mW]	Typical Operating Current [mA]
AC1401-0700-YYYY-ZZ	700	1150	650	1000
AC1401-0600-YYYY-ZZ	600	1000	540	900
AC1401-0500-YYYY-ZZ	500	800	450	720

The component complies with all applicable portions of 21 CFR 1040.10, 21 CFR 1010.2 and 21 CFR 1010.3. Since this is a component, it does not comply with all of the requirements contained in 21 CFR 1040.10 and 21 CFR 1040.11 for complete laser products.

The information published in this datasheet is believed to be accurate and reliable. Gooch and Housego reserves the right to change without notice including but not limited to the design, specification, form, fit or function relating to the product herein. ©2013 Gooch and Housego. All rights reserved.